

Solis-110K-5G-PRO

Solis Three Phase Inverters

>> Models:

Solis-110K-5G-PRO



Efficient

- 6/8 MPPTs, max. efficiency 98.7%
- > 150% DC/AC ratio
- Compatible with bifacial modules

Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life

Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector
- Supports aluminium wire access to reduce cost

DATASHEET**Solis-110K-5G-PRO****Models****110K****Input DC**

Max. input voltage	1100 V
Rated voltage	600 V
Start-up voltage	180 V
MPPT voltage range	160-1000 V
Max. input current	36 A / 32 A / 36 A / 32 A / 36 A / 32 A / 36 A / 32 A
Max. short circuit current	8*50 A
MPPT number/Max. input strings number	8/16

Output AC

Rated output power	110 kW
Max. apparent output power	121 kVA
Max. output power	121 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V
Rated grid frequency	50 Hz / 60 Hz
Rated grid output current	167.1 A / 158.8 A
Max. output current	183.8 A
Power factor	>0.99 (0.8 leading - 0.8 lagging)
THDi	<3%

Efficiency

Max. efficiency	98.7%
EU efficiency	98.3%

Protection

DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	DC Type II / AC Type II
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Strings monitoring	Yes
I/V Curve scanning	Yes
Integrated DC switch	Yes
Integrated AFCI (DC arc-fault circuit protection)	Yes ⁽¹⁾

General Data

Dimensions (W*H*D)	1183*585*363 mm
Weight	93 kg
Topology	Transformerless
Self-consumption (night)	<2 W
Operating ambient temperature range	-30 ~ +60°C
Relative humidity	0-100%
Ingress protection	IP66
Cooling concept	Intelligent redundant fan-cooling
Max. operation altitude	4000 m
Grid connection standard	G99, IEC61727
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4

Features

DC connection	MC4 connector
AC connection	OT terminal (max. 240 mm ²)
Display	LCD
Communication	RS485, Optional: Wi-Fi, GPRS, PLC

⁽¹⁾ Activation required.