

Solis-250K-EHV-5G

Solis Three Phase Inverters



Model:

800V: Solis-250K-EHV-5G



360 degree



Efficient

- ▶ 14 MPPTs, max. efficiency 99%
- ▶ 200% DC/AC ratio
- ▶ High power tracking density 63MPPT/MW
- ▶ Compatible with 500W+ bifacial modules



Smart

- ▶ Night SVG function
- ▶ Intelligent string monitoring. Smart I-V curve scan
- ▶ Remote firmware upgrade with simple operation



Safe

- ▶ IP66
- ▶ Built-in PID recovery for better module performance
- ▶ Fuse free design, safe and maintenance free
- ▶ Globally recognised branded component for longer life



Economic

- ▶ Power line communication (PLC) (optional)
- ▶ DC side supports "Y" connector
- ▶ Supports aluminium wire access to reduce cost
- ▶ Reserve DC energy storage access

Datasheet

Model Name	Solis-250K-EHV-5G
------------	-------------------

Input DC

Max. input voltage	1500 V
Rated voltage	1080 V
Start-up voltage	600 V
MPPT voltage range	580-1500 V
Max. input current	14*26 A
Max. short circuit current	14*40 A
MPPT number/Max. input strings number	14/28

Output AC

Rated output power	250 kVA @ 30°C / 235 kVA @ 40°C / 220 kVA @ 50°C
Rated grid voltage	3/PE, 800 V
Grid voltage range	640-920 V
Rated grid frequency	50 Hz / 60 Hz
Max. output current	180.4 A
Power Factor	>0.99 (0.8 leading - 0.8 lagging)
THDi	<3%

Efficiency

Max. efficiency	99.0%
EU efficiency	98.7%

Protection

DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	DC Type II / AC Type II
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Strings monitoring	Yes
I/V Curve scanning	Yes
Night time SVG function	Yes
Anti-PID function	Yes
Integrated DC switch	Yes

General Data

Dimensions (W*H*D)	1125*770*384 mm
Weight	113 kg
Topology	Transformerless
Self consumption (night)	<2 W
Operating ambient temperature range	-25 ~ +60°C
Relative humidity	0-100%
Ingress protection	IP66
Cooling concept	Intelligent redundant fan-cooling
Max. operation altitude	4000 m
Grid connection standard	EN50549, G99, AS4777.2, VDE0126, IEC61727, VDE4110, CEA 2019
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4

Features

DC connection	MC4 connector
AC connection	OT terminal (max. 300 mm ²)
Display	LCD
Communication	RS485, Optional: PLC