

Solis-80K-5G

Solis 5G Three Phase Inverters



360 degree

Features:

- ▶ 98.7% Max. efficiency
- ▶ Wide voltage range and low startup voltage
- ▶ 9 MPPT design with precise MPPT algorithm
- ▶ THDi<3%, low harmonic distortion against grid
- ▶ Anti-resonance, supporting over 6MW paralleled in one transformer
- ▶ Perfect commercial site monitoring solution
- ▶ Intelligent redundant fan-cooling
- ▶ Strings intelligent monitoring, Smart I-V Curve Diagnosis supported
- ▶ Fuse free design to avoid fire hazard
- ▶ Type II surge arrester for both DC and AC, type I surge arrester optional
- ▶ Leakage current repression technology
- ▶ Volt-watt work mode integrated
- ▶ DC input reverse alarm
- ▶ Optional anti-PID function integrated
- ▶ Integrated DC switches, AC switch optional



Model:

400V: Solis-80K-5G

Datasheet

Model Name	Solis-80K-5G
Input DC	
Recommended max. PV power	120kW
Max. input voltage	1100V
Rated voltage	600V
Start-up voltage	195V
MPPT voltage range	180-1000V
Max. input current	9*26A
Max. short circuit current	9*40A
MPPT number/Max. input strings number	9/18
Output AC	
Rated output power	80kW
Max. apparent output power	88kVA
Max. output power	88kW
Rated grid voltage	3/N/PE, 220/380 V, 230/400 V
Rated grid frequency	50/60Hz
Rated grid output current	121.6A
Max. output current	133.7A
Power Factor	>0.99 (0.8 leading - 0.8 lagging)
THDi	<3%
Efficiency	
Max. efficiency	98.7%
EU efficiency	98.3%
Protection	
DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection	DC Type II / AC Type II (AC Type I optional)
Grid monitoring	Yes
Anti-islanding protection	Yes
Temperature protection	Yes
Strings monitoring	Yes
I/V Curve scanning	Yes
Anti-PID function	Yes
Integrated DC switch	Yes
Integrated AC switch	Optional
General Data	
Dimensions (W*H*D)	1050*567*314.5 mm (with AC switch)
Weight	82kg
Topology	Transformerless
Self consumption	<2W (night)
Operating ambient temperature range	-25 ~ +60°C
Relative humidity	0-100%
Ingress protection	IP66
Cooling concept	Intelligent redundant fan-cooling
Max. operation altitude	4000m
Grid connection standard	VDE-AR-N 4105, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G98, G99, EN 50549-1/-2, RD 1699, UNE 206006, UNE 206007-1, IEC 61727, DEWA
Safety/EMC standard	IEC 62109-1/-2, IEC 62116, EN 61000-6-2/-4
Features	
DC connection	MC4 connector
AC connection	OT terminal (max. 185 mm ²)
Display	LCD, 2×20 Z
Communication	RS485, Optional: Wi-Fi, GPRS, Ethernet, PLC